

TECHNOVATION ANALYTICAL INSTRUMENTS PVT. LTD. W-312, 13" Cross Road, M.I.D.C., Rabale, Navi Mumbai-400701, Maharashtra, India.

W-312, 13 Cross Road, M.I.D.C., Rabale, Navi Mumbai-400701, Manarashtra, in Tel.: 9967177429 / 9870675538. CIN NO: U99999MH1990PTC057660 ISO 9001:2015

E-mail : taiplem@gmail.com Website: www.technovationindia.com

SERIES 87 PERSONAL SAFETY

THE INSTRUMENT

SERIES 87 offers personal gas alarms which are handheld. The instruments work on a 9 volts disposable dry cell. They have two alarms both audible and visual and low battery indication. SERIES 87 are fitted with highly reliable & reputed electrochemical sensors

FEATURES

- Two Audible & Visual Alarms, Settable by the user either high or low. Set level viewable
- Digital display, easy to read and operate.
- Small, Light-weight, Compact and Rugged.
- Works on disposable 9 V Dry cell.
- Electrochemical Sensors of repute & reliability

APPLICATIONS

Everyone, nowadays is aware of the need for environmental monitoring in the workplace atmosphere, especially where pollutants or toxic gases are encountered. Levels of concentration of toxic gases above the Occupational Exposure Limit lead to problems of health & safety of personnel. Oxygen deficiency of breathing air in closed vessels & confined places is another personal hazard. For applications concerned with personnel safety, an instrument is usually required to signal alarms at two levels - the Short Term (STEL) and Long Term (TWA) Exposure Limits. These limits are the responsibility of different bodies, so the precise level and definition of each varies.

POCKET SIZE ALARMS TECHNOVATION SAFETY GAS ALARM



TECHNOVATION® SR 87 STANDARD SPECIFICATIONS

Display	: 3 ¹ /digit LCD
Size	: 13 X 7 X 4.5 CM
Weight	: 250 gms. approx.
Power	: 9 V Cell PP3 type
Case	: Robust ABS Antistatic.
Low Batt	: Low Batt alarm LED
	provided
Operating Temp.	: 0 - 50°C.
Calibration	: By calibration gas or
	factory set

ACCESSORIES

Operation Manual, Flow-thro' cap, Hand aspirator-bulb, and Carrying case, Cal Screwdriver.

OPTIONS EXTRA (To be specified while ordering)

- External sensor mounted at the cable end up to 6 meters
- With belt-clip & neck-strap

GAS	RANGE	RESOLUTION	STE L	TWA	T (90) SECONDS	
O2	0 - 25 %	0.1 %			< 20 SEC	
CO	0 - 1000 PPM	1 PPM	400	50	< 35 SEC	
H ₂ S	0 - 100 PPM	0.1 PPM	10	5	< 60 SEC	
SO ₂	0 - 20 PPM	0.1 PPM	4	2	< 30 SEC	
CL ₂	0 - 50 PPM	0.1 PPM	1	.5	< 80 SEC	
NO2	0 - 50 PPM	0.1 PPM	5	3	< 30 SEC	
HCN	0 - 30 PPM	1 PPM	10		< 80 SEC	
H2	0 - 1 %	0.01 %	-	-	<70 SEC	
NH3	0 -100 OR 1000 PPM	1 PP M	35	25	< 100 SEC	
OTHER GASES AND RANGES ON REQUEST						