



ESTD: 1990

TECHNOVATION Analytical Instruments Pvt. Ltd

W-312, 13th Cross road, M.I.D.C Rabale, Navi Mumbai 400701, Maharashtra, India.
Tel.: 9967177428 / +91-22-27691238

E-mail : taiplem@gmail.com • Website: www.technovationindia.com

ISO 9001:2015



Cert. No. QMS0720020347

SR2012 - PORTABLE MULTI GAS ANALYSER WITH INBUILT PUMP

THE INSTRUMENT

The TECHNOVATION SR2012 is small portable multi-gas analyser and can measure up to five different gases simultaneously. A variety of sensors can be connected which could include Electrochemical, NDIR, Pellistor for a wide range of parameters. The 128x64 pixel LCD display makes operation easy and user friendly. Facility for storage, Viewing of saved data on display. The instrument is known for its superior performance, simplicity of use and long service life.

FEATURES

- Five sensors can be connected in the following configuration. Upto 4 Electrochemical. Plus upto 2 NDIR or Pellistor
- Name, Range and Resolution for each gas configurable
- 128x64 pixel LCD back light display
- Trend analysis, Alarms Error and event viewing
- Two Alarms, their set point, Activation, Hysteresis are
- Inbuilt pump with flow of 1.5 LPM and suction of 8" Hg column

APPLICATIONS

Process gas monitoring, Quality assurance, R&D applications, Purified BIO-gas. Modified atmosphere packaging ETC...

PRINCIPLE OF OPERATION

As a wide range of gases can be monitored, by selecting the appropriate sensor while ordering, All the gases are not mentioned here. Albeit the more common ones are, O₂, CO, H₂S, SO₂, Cl₂, NO, NO₂, C₂H₄, and other Toxic gases, Combustible Gases, NDIR sensors include CH₄, CO₂, Freon, etc..

OPTIONS

Please contact our sales team for specific applications Specific Gases, Ranges and options

LOW-COST DURABLE ACCURATE WITH GOOD AFTER-SALES-SERVICE



TECHNOVATION® SR2012 STANDARD SPECIFICATIONS

- Dases & Sensor : Electrochemical, Or NDIR, , types
Combustible gas pellistor.
- Range and Resolution : As per sensor selected
- Power : Battery pack 6V 3000mAh
- Display : 128x64 LCD with backlight
- Box size : 220x160x110 mm
- Weight : 2kg nett
- Box material : Aluminium cast
- Carrying case : Soft case provided
- Inbuilt Pump : 1.5 LPM suction of 8" Hg col

ACCESSORIES

Filter absorber tube, Battery charger, Instruction Manual

Typical sensors and ranges that may be used			
Gas	Range	Resolution	Sensor type
Oxygen	0-25 %	0.1%	Electrochemical
Carbon Monoxide	0-200 ppM	1 ppM	Electrochemical
Hydrogen Sulphide	0-200 ppM	0.1 ppM	Electrochemical
Combustible gases	0-100% LEL	1 % LEL	Pellistor
Carbon Dioxide	0-5%	0.01%	Non Dispersive Infra Red