



ESTD. 1990

## TECHNOVATION ANALYTICAL INSTRUMENTS PVT. LTD.

W-312, 13<sup>th</sup> Cross Road, M.I.D.C., Rabale, Navi Mumbai-400701, Maharashtra, India.  
Tel.: 9967177429 / 9870675538. CIN NO: U99999MH1990PTC057660

E-mail : [taiplem@gmail.com](mailto:taiplem@gmail.com) Website: [www.technovationindia.com](http://www.technovationindia.com)

ISO 9001:2015



Cert. No. QMS0720020347

# MODEL FEM - 15 COMPACT PORTABLE FUEL EFFICIENCY MONITOR

## THE INSTRUMENT

The 128X64 Graphic LCD display and fully menu driven to ensure simplicity in use. Trouble-free performance, cost effectiveness and reliability. Stored data can be viewed or downloaded to a computer. through an USB C port

## FEATURES

- Measured parameters: Oxygen, & Temperature. Optionally three additional gases based on Electrochemical sensors, CO<sub>2</sub> gas based on NDIR sensor and One Pellistor sensor can also be incorporated. Please see table for gases. .
- Stored parameters: Date, Time, and all selected parameters of each reading is data logged
- Data stored and can be downloaded to a computer for permanent storage and subsequently printed.
- Report Menu to View specific range of readings
- Calculated Parameters: CO<sub>2</sub> if sensor not installed. Excess Air, Total efficiency and Heat Losses of four different types, among others.
- User programmable for three non-conventional fuels. (One each for solid, liquid & gaseous fuels)
- Rubber jacket provided for instrument.
- Data for twenty-eight standard fuels preprogrammed.
- Elegant Gas cum Temperature probe with integral filter and cooler. Molded hose of 1m length.
- Auto and Manual sampling modes
- Auto Oxygen Calibration on request.
- Auto power OFF

## APPLICATIONS

Measurement of exhaust gases of Boilers, Furnaces, Heaters, Kilns in order to improve combustion efficiency and reduction of pollutant gases released by these devices

## STANDARD SPECIFICATIONS

Display	: 128x64 Graphic LCD display with back light
Power	: 3.7 V LiON rechargeable Battery
Low battery	: Indication provided.
In-Built Pump	: 5" Hg suction, 0.7 LPM flow
Working Temp.	: 5 TO 45 °C
Size & Wt	: 23x13x4.5cm & 0.8kg.
Keys	: Power and 3 navigation keys
Temp. probe	: Thermocouple, K type
MOC	: ABS plastic case.

## OPTIMIZE COMBUSTION EFFICIENCY

## ANALYSE DATA AND SAVE MONEY



## TECHNOVATION<sup>®</sup> MODEL FEM-15 STANDARD SPECIFICATIONS CONTINUED

Sensors	: Electrochemical. NDIR and pellistor options. Expected life for O <sub>2</sub> is 2 yrs & EC is 3 yrs.
Probe	: Gas Cooler and filter integral
Probe length	: 50cm Tube with integral thermocouple
Data storage	: Upto 400 readings
Data output	: USB -C port.
Indicators	: LEDs for Battery Charging, Rx, Tx, Lo Bat, Fault, Confidence Flash and Pump
Gases & Ranges	: Instrument supplied with Oxygen & temperature sensors, additional sensors available as per table below

## ACCESSORIES

Instrument manual, Battery Charger USB C type, Probe assembly, Interconnecting Hose (1.0 m length, Carrying case.

## OPTIONAL EXTRA

- Parameters other than Oxygen and temperature. Gases – as listed below.

SENSOR	STANDARD GASES		OPTIONAL GASES				
	EC	TC	ELECTROCHEMICAL			NDIR	PELISTER
GAS	O <sub>2</sub> %	TEMP °C	CO PPM	SO <sub>2</sub> PPM	NO <sub>2</sub> PPM	CO <sub>2</sub> %	HC(CH <sub>4</sub> )
RANGE	0 - 25	0-450	0 - 2000	0-20	0 - 20	0 - 20	0-5 %
RESOLUTION	0.1	1	1 ppm	0.1	0.1	0.1	0.01 %